

EIFS CLEANER For Synthetic Stucco

Description

This product is extremely effective for cleaning and removing stains, scale and other mineral deposits from PLEKO[®], DRYVIT[®], STO[®], PAREX[®], SYNERGY[®], FINESTONE[®], SUREWALL[®] Elastocoat and other natural and synthetic stucco and masonry surfaces. It is highly concentrated and may be used in diluted form. Can be brushed or sprayed on surface. This product will clean with ease and save time and money.

Features

- Fast Acting
- Economical
- Brush or Spray On
- Highly Concentrated
- Safe for All EIFS Surfaces
- Safe for All Masonry Surfaces

Use And Directions

Dilute from 1 part up to 4 parts water, depending on condition of surface to be cleaned. One gallon of product (diluted 1 to 4) will cover approximately 800 sq. ft. of surface. This estimation of coverage depends on porosity and texture of the surface.

Pre-wet surface to be cleaned and spray or brush on. Let stand up to 5 minutes, thoroughly agitate with stiff bristle brush and rinse off.

Use adequate protection as indicated in handling and storage label statement and use only in plastic spray guns. Rinse out sprayer thoroughly after each use.

Physical Properties

Physical Form:	Water thin liquid	Specific Gravity:	1.075
Appearance:	Clear	pH:	< 1.0
Color:	Pale Yellow	Evaporation Rate (Water = 1):	1.0
Odor:	Characteristic "acidic"	Flash Point (T.C.C.):	None

143EC - 0708